

SECTION 10 14 19  
SIGNAGE

PART 1 – GENERAL

1.1 SUMMARY

- A. This section includes the following types of signs:
  - 1. Room Identification signs.
  - 2. Signs w/ inserts
  - 3. Exterior signs

1.2 ACTION SUBMITTALS

- A. Product Data: For each type of product.
- B. Shop Drawings: For dimensional letter signs.
  - 1. Include fabrication and installation details and attachments to other work.
  - 2. Show sign mounting heights, locations of supplementary supports to be provided by others, and accessories.
  - 3. Show message list, typestyles, graphic elements, and layout for each sign at least half size.
- C. Samples: For each exposed product and for each color and texture specified.
- D. Sign Schedule: Use same designations specified or indicated on Drawings or in a sign schedule.

1.3 PROJECT CONDITIONS

- A. Field Measurements: Take field measurements prior to preparation of shop drawings and fabrication to ensure proper fitting. Show recorded measurements on final shop drawings. Coordinate fabrication schedule with construction progress to avoid delay.

PART 2 - PRODUCTS

2.1 PANEL SIGNS

- A. Provide signs as scheduled, and as shown on drawings.
  - 1. Produce smooth, even, level sign panel surfaces, constructed to remain flat under installed conditions within a tolerance of plus or minus 1/16 inch measured diagonally.
- B. Panel Signs: Fabricate signs with edges mechanically and smoothly finished to conform with the following requirements:
  - 1. Match CAMPUS Standards (see drawings.)

NAME OF BUILDING (BLDG XXX)

Xavier University

Cincinnati Ohio

- a) **3/8" THICK PVC,**
  - b) **Color: Benjamin Moore #OC-63 "Winter Snow"**
2. Provide inserts as required.

D. Graphic Content and Style: Provide sign copy that complies with the requirements indicated for size, style, spacing, content, position, material, finishes, and colors of letters, numbers, and other graphic devices.

E. Raised Copy: Machine-cut copy characters from matte-finished opaque acrylic sheet and chemically weld onto the acrylic sheet forming sign panel face. Produce precisely formed characters with square cut edges free from burrs and cut marks.

1. Panel Material: Matte-finished opaque acrylic sheet.
2. **Raised Copy Thickness: Not less than 1/32 inch.**
3. **Color: Sherwin Williams SW 7048 "Urbane Bronze"**

F. Wall-Mounted Panel Signs: Attach panel signs to wall surfaces using the methods indicated below:

1. Two-Face Tape: BETWEEN SIGN AND WALL. No shim. Clean bond-breaking materials from substrate surface and remove loose debris. Apply tape strips symmetrically to back of sign and of suitable quantity to support weight of sign without slippage. Keep strips away from edges to prevent visibility at sign edges. Place sign in position, and push to engage tape adhesive.

### PART 3 - EXECUTION

#### 3.1 INSTALLATION

- A. Locate sign units and accessories where indicated, using mounting methods of the type described and in compliance with the manufacturer's instructions.
  1. Install signs level, plumb, and at the height indicated, with sign surfaces free from distortion or other defects in appearance.

#### 3.2 INTERIOR SIGN SCHEDULE / See drawings for locations, dimensions and layout of signage.

END OF SECTION 10 14 00